

Filed by Express Mail
(Receipt No. 010803089)
on 02/27/2001
pursuant to 37 C.F.R. 1.10.
by [Signature]

DRAWING METHOD FOR DRAWING IMAGE ON TWO-DIMENSIONAL SCREEN

The subject application is related to subject matter disclosed in the Japanese Patent Application No. Tokugan 2000-399461 filed on December 27, 2000 and Tokugan 2001-236325 filed on August 3, 2001 in Japan, based on which this application claims priority under the Paris Convention and which is incorporated by reference herein.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a drawing method for drawing an image on a two-dimensional screen such as on a television monitor device and a drawing device therefore, a computer readable recording medium having recorded therein a draw processing program to be executed on a computer, a program execution device for executing the draw processing program, and a draw processing program to be executed on a computer.

2. Description of the Related Art

There are accelerating trends toward higher integration and higher speed as for processors, memories and so forth of recent television game machine and personal computer. Such advancement enables real-time generation

of a three-dimensional image having an excellent presence and perspective (feel of depth) and display thereof on a two-dimensional monitor screen.

For the case a three-dimensional image is drawn on a two-dimensional monitor screen, it is a general practice to subject a three-dimensional polygonal data to geometric processing such as coordinate transformation, clipping and lighting, and the obtained data are then transformed by perspective projection transformation.

For the case a three-dimensional image is drawn on a two-dimensional monitor screen, a widely adopted technique for expressing perspective or reducing affection by flicker caused by shrunk drawing of distant polygons is such that drawing the image in focus at a portion close to a virtual viewpoint but blurred at a portion distant from the virtual viewpoint.

In a conventional method for drawing a blurred image depending on the distance thereof from the virtual viewpoint, an original image are, for example, stepwisely shrunk corresponding to the distance from a virtual viewpoint and then enlarged again, and the enlarged images is synthesized with the original image according to distance in the depth direction (Z value) from the virtual viewpoint set for every pixel.

Such stepwise shrinking depending on the distance from the virtual viewpoint and corresponding enlargement,

however, increases a load of image processing by the CPU, which will adversely affect other processing in progress of a game.

On the other hand, reducing the number of steps of shrinking and enlargement in the blurring in order to reduce the load of the CPU will be unsuccessful in obtaining a desired blurring effect and will thus fail in obtaining a desirable perspective.

SUMMARY OF THE INVENTION

The present invention was proposed to address the foregoing problems, and an object thereof resides in that providing a drawing method, a drawing device, a computer readable recording medium having recorded therein a draw processing program to be executed on a computer, a program execution device for executing the draw processing program, and a draw processing program to be executed on a computer; all of which are aimed at reducing load on a CPU when an image is drawn as being blurred depending on distance from a virtual viewpoint, and at obtaining a desired blurring depending on the distance from the virtual viewpoint to thereby create a desirable perspective.

In the present invention, a value for expressing distance from a virtual viewpoint is set for every compositional unit of a first image, a second image is generated, a coefficient corresponding to such value for

expressing the distance set to every predetermined compositional unit is defined, and the first image and the second image are then synthesized based on the coefficient defined for every predetermined compositional unit.

5 In particular in the present invention, the first image is blurred to generate the second image, and the first image and the second image are synthesized using a semi-transparent coefficient such that increasing a ratio of the second image as the distance from the virtual
10 viewpoint increases, so that an image can be obtained as being in focus at a portion close to a virtual viewpoint and blurred to a larger extent at a portion apart further from the virtual viewpoint.

Other and further objects and features of the present
15 invention will become obvious upon understanding of the illustrative embodiments about to be described in connection with the accompanying drawings or will be indicated in the appended claims, and various advantages not referred to herein will occur to one skilled in the
20 art upon employing of the invention in practice.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing an exemplary schematic constitution of a major portion of a drawing
25 device according to an embodiment of the present invention;

Fig. 2 is a chart for explaining a general CLUT (Color

Look-Up Table);

Fig. 3 is a chart for explaining index for defining R, G and B from the CLUT;

Fig. 4 is a chart for explaining CLUT containing
5 gradational α values;

Fig. 5 is a chart for explaining a Z value expressed in three bytes;

Fig. 6 is a graph for explaining a case in which the second byte of the Z value is adopted as an index for
10 defining the α value from the CLUT of this embodiment;

Fig. 7 is a flow chart showing a schematic process flow in a draw processing in this embodiment;

Fig. 8 is a chart showing an exemplary current image before being added with perspective;

Fig. 9 is a chart showing an exemplary blurred image obtained by entirely blurring the current image;

Fig. 10 is a chart showing an exemplary image having a natural perspective generated by the draw processing of this embodiment; and

20 Fig. 11 is a block diagram showing a schematic constitution of a personal computer for executing a draw processing program whose process flow was shown in Fig. 7.

25 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Various embodiments of the present invention will be

described with reference to the accompanying drawings. It is to be noted that the same or similar reference numerals are applied to the same or similar parts and elements throughout the drawings, and the description of the same or similar parts and elements will be omitted or simplified.

Constitution of Drawing Device According to the Present Embodiment

Fig. 1 shows an exemplary schematic constitution of a major portion of a drawing device 1 according to an embodiment of the present invention.

The drawing device 1 now in this embodiment is such that for drawing a two-dimensional image based on texture mapping onto three-dimensional polygons, and is applicable, for example, to television game machine, personal computer and three-dimensional graphical device (in particular to so-called graphic synthesizer).

The drawing device 1 of this embodiment shown in Fig. 1 mainly comprises a luminance calculation/coordinate transformation unit 2, an LOD (Level OF Detail) calculation unit 3, a texture coordinate calculation unit 4, a DDA (Digital Differential Analyzer) unit 5, a pixel engine 6 and an image memory 7.

The image memory 7 further comprises the individual storage regions, that is, a Z buffer 8 for storing values in the depth direction from a virtual viewpoint (typically expressed with 3 byte, 24 bits in total), a texture buffer

9 for storing data such as texture for generating by mapping
an entire color and pattern on polygons and CLUT (Color
Look-Up Table), and a frame buffer 10 for storing and
synthesizing frame data displayed on a two-dimensional
5 monitor screen.

To an input terminal 13 of the drawing device 1
provided with such components, various information for
drawing a three-dimensional image, such as those for
polygon, texture, light source and viewpoint, are entered.
10 Such various information is supplied through a
communication line, storage device and so forth.

The three-dimensional polygon information comprises
those, for example, of coordinates (x, y, z) for the
individual vertices of a triangular polygon and normal
15 lines at the individual vertices; and the viewpoint
information and the light source information are those for
enabling luminance calculation and coordinate
transformation with regard to such polygon. Now the light
source information is by no means limited to that for
20 expressing information for a single light source but also
may be such that expressing information for a plurality
of light sources.

The texture information comprises information for
texture coordinate corresponding to the individual
25 vertices of the triangular polygon and CLUT used for
expressing color or pattern.

The CLUT herein is composed of a three-primary-color table for R (red), G (green) and B (blue), and an α value table. The three-primary-color table is used for defining colors of the individual pixels in the texture. The α value is a coefficient for expressing semi-transparency, which is responsible for defining a ratio of image blending (α blending) when the texture is mapped. In this embodiment, the α values in the CLUT are graded in a plurality of steps, where details of which will be described later. The table number of the CLUT and the α value are correlated so that a larger table number corresponds to a smaller (or a larger) α value.

An index for withdrawing three-primary-color values for R, G and B from the CLUT (that is, a value for designating a table number of the CLUT) is set for every pixel expressed by an XY coordinate of the texture. In particular for the case of this embodiment according to the present invention, while details of which will be described later, the second byte of the Z value (expressed with 3 bytes, 24 bits in total) for the individual pixels is used as an index for withdrawing the α value from the CLUT. In this embodiment, the Z value is set so as to be smaller as the distance from a virtual viewpoint becomes larger.

Such a variety of information is first entered into the luminance calculation/coordinate transformation unit 2 of the drawing device 1.

The luminance calculation/coordinate transformation unit 2 transforms the entered individual coordinate information of polygons into coordinate values in another coordinate system for two-dimensional drawing, and calculates the luminance at the individual vertices of the polygons based on the viewpoint information and light source information. The luminance calculation/coordinate transformation unit 2 is also responsible for other processing beside such calculation. The individual values calculated by the luminance calculation/coordinate transformation unit 2 are then entered into the LOD calculation unit 3.

The LOD calculation unit 3 calculates an LOD (Level Of Detail) value, which is used when the pixel engine 6 reads out a texture from the texture buffer 9, using the Z coordinate of thus-transformed polygon. Now the LOD value is a value calculated from a reduction ratio according to which the polygon is shrunk, and typically obtained as a logarithmic value of a distance from the viewpoint to the polygon. The obtained LOD value is then sent via the DDA unit 5 to the pixel engine 6.

The texture coordinate calculation unit 4 calculates a texture coordinate value used when the pixel engine 6 reads out a texture from the texture buffer 9. The obtained texture coordinate value is then sent via the DDA unit 5 to the pixel engine 6.

The DDA unit 5 transforms the two-dimensional polygon vertices information, Z coordinate values, luminance information and so forth into pixel information. More particularly, for the individual pixels, coordinate values 5 thereof, Z values, luminance values and texture coordinate values are sequentially defined based on linear interpolation. The output from the DDA unit 5 is then sent to the pixel engine 6.

The pixel engine 6 controls read/write operations to 10 or from the Z buffer 8, texture buffer 9 and frame buffer 10; and is also responsible for texture mapping, comparison of Z coordinate values, pixel value calculation and so forth.

The pixel engine 6 not only withdraws 15 three-principal-color data of R, G and B from the CLUT corresponding to the index of the texture to thereby set color for the individual pixels, but also withdraws α values, which is later used for α blending, from the CLUT using the second byte of the Z value of the individual pixels, 20 detailed process flow of which will be described later.

The pixel engine 6 is also responsible for various processing such as scissoring, dithering and color clamping. The scissoring refers to a processing for removing data overflowed from the displayable area; the 25 dithering refers to a processing for complicating arrangement of each color in order to express many colors

using only a small number of principal colors; and the color clamping refers to a processing for limiting the calculated color value so as not to exceed 255 or become smaller than zero.

5 Image data obtained after such processing by the pixel engine 6 are stored into the frame buffer 10 to thereby generate frame data to be drawn on the two-dimensional monitor screen (two-dimensional image data), and such two-dimensional image data is then read out from the frame
10 buffer 10, output from an output terminal 14, and sent to the two-dimensional monitor device.

Draw Processing of the Embodiment

Details of the CLUT according to this embodiment, setting of texture color or pattern using such CLUT, and
15 the α blending will be explained in comparison with setting of texture color or pattern using a general CLUT and the α blending.

Typical Draw Processing using General CLUT

Prior to explanation of an exemplary drawing using
20 CLUT according to this embodiment, relation between the three-principal-color data for R, G and B and α value in a general CLUT will be explained. Fig. 2 shows a typical example of a general CLUT, and Fig. 3 shows an XY coordinate of individual pixels composing the texture and an example
25 of indices for defining color or pattern of such individual pixels.

The CLUT shown in Fig. 2 comprises table numbers (No.), color data for R, G and B, and α values (values listed in column "A"). The table numbers, color data for R, G and B, and α values are respectively expressed in hexadecimal numbers. The table numbers are those specified by the index of the individual pixels; values of the color data for R, G and B indicate levels of such three principal colors; and α values indicate the degree of semi-transparency.

Referring now to Figs. 2 and 3, index "00" in Fig. 3 corresponds to table No. "00" in Fig. 2; index "01" to table No. "01"; index "02" to table No. "02"; index "03" to table No. "03" and so on. The individual pixels having index of "00" in Fig. 3 are assigned with a color of R (red), which is apparent from Fig. 2 showing that table No. "00" corresponds to "ff" for R, "00" for G and "00" for B. Similarly, the individual pixels having index of "01" in Fig. 3 are assigned with a color of G (green), which is apparent from Fig. 2 showing that table No. "01" corresponds to "00" for R, "ff" for G and "00" for B. Thus an exemplary texture drawn according to Figs. 2 and 3 appears as a green cross on a red background.

According to the CLUT shown in Fig. 2, the individual pixels having index of "00" in Fig. 3 are assigned with an α value of "80" which is corresponded to table No. "00" in Fig. 2, and similarly, the individual pixels having index

of "01" in Fig. 3 are also assigned with an α value of "80" which is corresponded to table No. "01" in Fig. 2. Such α value of "80" represents a degree of semi-transparency of approx. 0.5 (i.e., 50%), so that the green cross on the red background is drawn so as to overlap an already-drawn image in a 50% transparency.

As is clear from the above, using the general CLUT and indices shown in Figs. 2 and 3 allows determination only of color or pattern of the texture and the ratio of image blending in the α blending.

Typical Draw Processing using CLUT of the Embodiment

While Figs. 2 and 3 in the above showed a general CLUT and a typical use thereof, the embodiment of the present invention employs a CLUT having α values gradationally composed therein and a predetermined value in the Z value for the individual pixels as indices for defining the α values in the CLUT (the second byte of a three-byte Z value as shown in Fig. 5 in this embodiment) to thereby allow the α blending according to distance in the depth direction of drawn objects from a virtual viewpoint. Determination of color or pattern of the texture can be proceeded as described in the above referring to Figs. 2 and 3.

That is, in this embodiment, the α values in the CLUT are gradationally set so that the larger value thereof corresponds to higher semi-transparency (lower

transparency), and the second byte of the Z value, whose value decreases as the distances from the virtual viewpoint increase, is used as an index for selecting the α values, to thereby determine an α plane. The α blending, using
5 such α plane, of a current image and a blurred image thereof, for example, can provide an image in which an object or the like close to the virtual viewpoint is in focus and those apart from the virtual viewpoint are gradually blurred as the distance from such virtual
10 viewpoint increases.

In other words, the embodiment can provide an image in which an object or the like close to the virtual viewpoint is well focused and those apart from the virtual viewpoint are gradually blurred as the distance from such virtual
15 viewpoint increases, just like an image obtained by photographing while focusing on an object close to the viewpoint under setting of a shallow depth of field, where even objects or the like apart from the focal position retain the color to thereby attain a natural perspective.
20 Such image totally differs from a pan-focal image well focused irrespective of the distance from a viewpoint, which is obtainable by photographing using a photographic optical system while setting a large depth of field of a photographing lens.

25 A reason why in this embodiment the second byte of the Z value expressed with 3 bytes (24 bits) as shown in

Fig. 5 is used as an index for defining the α values of the CLUT shown in Fig. 4 is that the amount of change of the Z value is in inverse proportion to that for bit values in the individual bytes as shown in Fig. 6. As is clear from Fig. 6, using the least significant byte of the Z value will result in too large changes in the bit values, and looping of the bit value may occur in a worst case in which the same bit values may repetitively be generated. On the other hand, using the most significant byte of the Z value will result in too small changes in the bit values. Thus the second byte of the Z value is to be used as an index for defining the α values of the CLUT.

That is, when a predetermined byte of the Z value is used as an index for defining the α values, too large changes in the index designated by such predetermined byte result in large changes also in the α values defined by such index, which undesirably sharpens changes in the α -blended image and ruins the natural perspective. When the looping of bits in the predetermined byte should occur, an appropriate relation between the distance from the virtual viewpoint and the α value can no more be retained and the obtained image will be denaturalized badly. On the other hand, too small changes in the index designated by such predetermined byte result in too small changes in the α values defined by such index, which only produces no significant change in the resultant α -blended image and

fails in producing a desirable perspective. For such reasons, the second byte of the Z value is used as an index for the α values in this embodiment, which can yield an appropriate perspective.

5 Flow of Draw Processing using CLUT and Z Values in the Embodiment

The following paragraphs describe, referring to a specific example of the drawing, a process flow of the draw processing capable of obtaining natural perspective by using the CLUT according to this embodiment (CLUT having gradationally composed α values) and the second byte of the Z value as an index for the α values.

Fig. 7 shows a schematic flow of the draw processing according to the embodiment. It should now be noted that the processing described below is such that being executed mainly by the pixel engine 6 using data stored in the image memory 7.

As shown in Fig. 7, the pixel engine 6 first in step S1 draws a current image (a first image in the present invention) into the frame buffer 10, and writes a Z value in the Z buffer 8.

The current image herein comprises a "mountain" object 20, a "house" object 21 and a "human" object 22, where the "mountain" object 20 is placed most apart from a virtual viewpoint, the "human" object 22 is placed close to the virtual viewpoint, and the "house" object 21 is

placed at an intermediate point therebetween, as shown in Fig. 8. A background image other than these objects is omitted herein for simplicity of the explanation.

The pixel engine 6 next in step S2 generates a blurred image of the current image (a second image in the present invention), and stores such blurred image into another storage area in the frame buffer 10. It is now also allowable to provide a separate frame buffer beside the frame buffer 10 and store the blurred image into such separate frame buffer. There is known a variety of techniques for producing the blurred image, and one example of which is such that synthesizing the current image with a slightly shifted image thereof.

The blurred image generated in step S2 is composed, for example, of a blurred image 23 of the "mountain" object 20 shown in Fig. 8, a blurred image 24 of the "house" object 21 and a blurred image 25 of the "human" object 22, as shown in Fig. 9. The degrees of the blurring of the blurred images 23, 24 and 25 are the same.

The pixel engine 6 next in step S3 reads out the α value from the CLUT shown in Fig. 4 using the second byte of the Z value, written in the Z buffer 8, for the individual pixels in the current image shown in Fig. 8.

As has been described in the above, in the current image shown in Fig. 8, the "mountain" object 20 is most apart from the virtual viewpoint, the "human" object 22

is most close to the virtual viewpoint, and the "house" object 21 is placed at an intermediate distance. So that the Z values for the individual pixels of the current image shown in Fig. 8 are largest for the pixels composing the "mountain" object 20, smallest for those composing the "human" object 22, and intermediate for the "house" object 21. When the second byte of such Z value is used as an index for withdrawing the α value from the CLUT shown in Fig. 4, the α value corresponding to the individual pixels is largest for those composing the "mountain" object 20 (maximum degree of semi-transparency), smallest for those composing the "human" object 22 (minimum degree of semi-transparency), and intermediate for those composing the "house" object 21 (intermediate degree of semi-transparency).

The pixel engine 6 next in step S4 proceeds the α -blending of the current image shown in Fig. 8 and the blurred image shown in Fig. 9, both of which being stored in the frame buffer 10, using an α plane composed of the α values read out in the process of step S3.

Since the degree of semi-transparency is largest for the individual pixels composing the "mountain" object 20, smallest for those composing the "human" object 22, and intermediate for those composing the "house" object 21 in such α plane, an image obtained by α -blending of the current image shown in Fig. 8 and the blurred image shown

in Fig. 9 is such that shown in Fig. 10.

More specifically, since the portion of the "mountain" object has the largest degree of semi-transparency, in which the blurred image accounts for a larger ratio than the current image, so that such object is drawn as a blurred image **26** as shown in Fig. 10. On the other hand, since the portion of the "human" object has the smallest degree of semi-transparency, in which the current image accounts for a larger ratio than the blurred image, so that such object is drawn as an in-focal image **28**. Since the portion of the "house" object has the intermediate degree of semi-transparency, so that such object is drawn as an image **27** not so well-focused than the image **28** but not so blurred than the image **26**.

It is now also allowable for the pixel engine **6** to practice the processing as shown by the flow chart of Fig. 7 on the hardware basis such as DSP (Digital Signal Processor), or on the software basis with the aid of draw processing programs such that being sent via a communication line such as CPU, or such that being read out by a storage device from a storage medium such as DVD or CD-ROM. In particular, a draw processing program used for the case that the draw processing by the pixel engine **6** is practiced on the software basis is such that sequentially executing the individual process steps explained referring to the flow chart of Fig. 7. Such draw

processing program can not only be installed previously as a processing program for the pixel engine 6, but can also be entered through the input terminal 13 shown in Fig. 1 at the same time with, or in advance of entering the polygon information.

As a specific example of a constitution for practicing the draw processing of this embodiment on the software basis, Fig. 11 shows a schematic constitution of a personal computer on which the draw processing program whose process flow was shown in Fig. 7 is run. Now in this embodiment, the draw processing program is mainly executed by a CPU 123 shown in Fig. 11.

In Fig. 11, a storage unit 128 comprises, for example, a hard disk and a driver therefore. The hard disk has stored therein an operating program; draw processing program 129 of this embodiment incorporated for example by installation from various recording media such as a CD-ROM and DVD-ROM, or downloading via a communication line; and various data 130 typically including graphic information for polygon drawing, texture, Z value, general texture, color value and α value.

The communication unit 121 is a communication device responsible for data communication with the external, such as a modem allowing connection to an analogue public telephone line, a cable modem allowing connection to a cable television network, a terminal adaptor allowing connection

to ISDN (Integrated Services Digital Network), and a modem allowing connection to ADSL (Asymmetric Digital Subscriber Line). A communication interface (I/F) unit **122** is an interface device responsible for protocol conversion which enables data exchange between the communication unit **121** and an internal bus.

An input unit **131** is an input device such as a keyboard, mouse and touch pad. A user interface (I/F) unit **132** is an interface device for supplying signals from the input unit **133** to the internal unit.

A drive unit **135** is a drive device capable of reading various data and programs including the draw processing program according to this embodiment from a recording medium such as a card-type semiconductor memory. A drive interface (I/F) unit **134** is an interface device for supplying signals from the drive unit **135** to the internal unit.

A display unit **137** is a display device such as a CRT (cathode ray tube) or LCD (liquid crystal display). A display drive unit **136** is a drive device responsible for driving such display unit **137** for display.

A ROM **124** typically comprises a re-loadable non-volatile memory such as a flash memory, and stores a BIOS (Basic Input/Output System) and various initial set values of the personal computer. A RAM **125** is a device into which application programs read out from the hard disk

in the storage unit 128 or various data are loaded, and is used as a working RAM for the CPU 123.

The CPU 123 controls the entire operations of the personal computer as well as executes the foregoing draw processing based on the operating system programs or the draw processing program 129 of this embodiment stored in the storage unit 128. That is, in the constitution shown in Fig. 11, The CPU 123 executes the draw processing program of this embodiment, which is one of the application programs read out from the hard disk of the storage unit 128 and loaded into the RAM 125, to thereby enable the draw processing described in the foregoing embodiment.

As has been described in the above, the embodiment can provide an image in which an object or the like close to the virtual viewpoint is well focused and those apart from the virtual viewpoint are gradually blurred as the distance from such virtual viewpoint increases, where even objects or the like apart from the focal position retain the color to thereby attain a natural perspective.

In the conventional drawing technique, blurred images were generated by multi-step shrinkage and the corresponding enlargement to thereby achieve the perspective, and such blurred images obtained from such multi-step processing were then synthesized with an original image, so that the amount of image processing could not be reduced. On the contrary in this embodiment, the

perspective is achieved by α -blending the current image and a single blurred image using an α -plane comprising α values corresponding to the distances from the virtual viewpoint, so that the amount of image processing does not increase even when the distance from the virtual viewpoint is expressed in 256 steps (1 byte), which desirably ensures load reduction for CPU and speed-up of the processing.

The embodiment described in the above is only part of the examples of the present invention. It is therefore to be understood that the present invention may be practiced in any modifications depending on the design or the like otherwise than as specifically described herein without departing from the scope and the technical spirit thereof.

For example, while a case of α -blending the current image and a blurred image using the α -plane was exemplified, such α -plane is also available for blending an arbitrary color with the current image, which produces an image in which the objects or the like seem to be fused into the arbitrary color as the distance from the viewpoint increases. Such technique is advantageous in achieving fogging, in which an object is more heavily fogged as the distance thereof from the viewpoint increases. It becomes also possible to create a special effect by α -blending an arbitrary image and the current image using such α -plane.

While the α value was defined based on the Z value for every pixel in the above embodiment, it is still also

allowable to define the α -value according to the distance from the virtual viewpoint for every polygon or object.

100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000